


1200 PROFILE

1000 Series



Cross-section dimensions:



THE STAR OF THE 1000 SERIES

This profile is designed to ensure that the LED source is invisible, offering uniform and soft lighting for the eyes. A compact and versatile luminaire!

FEATURES

- Designed to give a uniform light without hot spots* with an opal or prime lens.
- Custom length by sections of 2 to 240 inches (6m).
- Application guide for 10mm (3/8-inch) LED engine or less.
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED engine.
- Compatible with multiple installation accessories.
- Designed to meet North American woodworking standards.
- Conforms to UL STD. 2108 for closet usage.

OPTIONS



LED ENGINE COMPATIBILITY

IP22: Compatible with LED engines up to **14mm** wide.


























IP68: Compatible with LED engines up to **10mm** wide.
















LINEAR WEIGHT

0.099 lbs/ft, 0.148 kg/m (without lens)

*Dot free only in certain configurations - contact your sales representatives for information



PROFILE	LENSES	MOUNTING HARDWARE	MOTION SENSORS*	LENGTH
 1200 - 1200 Profile, alu	 CL - Clear lens	 FL - Flat bracket	 SENI - 30 sec. Embedded	Custom length by sections of 2 to 240 inches (6m).
 1201 - 1200 Profile, black	 SP - Spread lens	 45 - 45° Corner bracket	 SEN2 - 30 sec. Outside extrusion	
 1202 - 1200 Profile, white	 OX - Optiflex lens	 SW - Swivel bracket 180°	 SEN3 - 4 min. Embedded	
 120X - 1200 Profile, custom color IMPORTANT: Give RAL color No See Appendix 1 on page 256	 OP - Opal lens	 Easy beam angle adjustment	 SEN4 - 4 min. Outside extrusion	
RAL NUMBER	 PR - Prime lens	 3M - Mounting tape, double face	 SEN5 - Integrated proximity hand motion sensor	
	 BK - Black lens	 NO - No mounting hardware	 NO - No sensor	
	 FO - Focus lens		*NOTES All motion sensors: - Max 36W/12V or 72W/24V - Can only be used with non-dimmable power supplies	
	 SIL - Silens Serie 1000			
	 NO - No lens			
PROFILE	LENS	MOUNTING HARDWARE	MOTION SENSOR	LENGTH

COLOR TEMPERATURE	LUMEN PACKAGE*	LEAD IN/OUT	USAGE	POWER SUPPLY/CONTROL	*NOTES
<ul style="list-style-type: none">  24 - 2400K  27 - 2700K  30 - 3000K  35 - 3500K  42 - 4200K  53 - 5300K (LHP only)  62 - 6200K (LP only) 	<ul style="list-style-type: none"> LP0 - 128 LM / 1.5W FT / 90+CRI LP1 - 160 LM / 1.5W FT / 90+CRI LP2 - 255 LM / 3.0W FT / 90+CRI LP3 - 308 LM / 4.5W FT / 90+CRI LP4 - 400 LM / 5.8W FT / 90+CRI LHP - 700 LM / 7.0W FT / 95+CRI 	<ul style="list-style-type: none"> HW3 - Hardwire 3 FT HW6 - Hardwire 6 FT HW9 - Hardwire 9 FT HWX - Hardwire custom FT DC3 - DC plug 3 FT DC6 - DC plug 6 FT DC9 - DC plug 9 FT DCX - DC plug custom FT NO - No lead 	<ul style="list-style-type: none"> I - IP22 indoor dry location O - IP68 wet/damp location (IP68 is not available for motion sensor option) 	<ul style="list-style-type: none"> A - Non-dimming B - ELV dimming 120V AC C - ELV dimming 120/277 VAC** D - 0/10V dimming 120/277 VAC E - Non-dimming DC plug in F - DMX G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC NO - No driver 	<ul style="list-style-type: none"> *The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and translucency conversion factors. ** Only available in 96W - 24V Driver.
<ul style="list-style-type: none">  WD1 - 2200-2700K 14W  WD3 - 2700-3500K 14W  TW1 - Tunable White 11W  TW2 - Tunable White 19W  RGB1 - RGB 14W  RGB2 - RGB 19W  RGBW2 - 3000K 4in1 	Lumen Package selection is not available for WD , TW and RGB color options.	For TW or RGB strip options, select either A [Non-dimming] or E [Non-dimming DC plug] in power supply plus the J [Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC] controller.			
COLOR TEMPERATURE CCT	LUMEN PACKAGE	LEAD IN LEAD OUT	USAGE	POWER SUPPLY/CONTROL	