


7500 PROFILE

7000 Series



Cross-section dimensions:



This 7500 series has direct, indirect or combined lighting options. Combining style and **elegance in a beautiful round format**, the 7500 profile is designed to be a suspended fixture with different and independent lumen package for both lighting options to achieve a wide variety of looks and lighting effects. This charming light fixture, is perfect for your project in either residential or commercial applications.

FEATURES

- Customizable lengths by sections from 2 to 240 inches (6m).
- Designed to give a uniform light without hot spots with a prime lens.
- Large variety of optics allows for greater creativity.
- 2 different suspension options; fixed and pivoting.
- Made of ALCOA 6063 T-5 aluminum alloy increasing heat dissipation.
- Increases the practical life of your LEDs with better heat dissipation.
- Designed to meet North American woodworking standards.

OPTIONS























LED ENGINE COMPATIBILITY






















Compatible with LED engines up to **12mm** wide.

LINEAR WEIGHT

0.433 lbs/ft, 0.644 kg/m (without lens)



PROFILE	LENS DOWN	LENS UP	MOUNTING HARDWARE	CANOPY	LENGTH
 7500 - 7500 Profile, alu	 OX - Optiflex lens	 CL - Clear lens	 SUS - Suspension kit with 15ft. aircraft cable	<p>NOTE: Only available with SUS bracket (suspension)</p>  Remote driver canopy plate See Appendix 2 on page 158 CR0 - Alu CR1 - Black CR2 - White	Custom length by sections of 2 to 96" Swivel maximum length = 72"
 7501 - 7500 Profile, black	 PR - Prime lens	 SP - Spread lens	 Suspension swivel kit with 15ft. aircraft cable SWRD - Red loop SWPK - Pink loop SWCY - Cyan loop SWBK - Black loop SWBL - Blue loop SWWH - White loop SWGR - Green loop SWTR - Transparent loop SWOR - Orange loop	 Integrated driver in canopy See Appendix 2 on page 158 CI0 - Alu CI1 - Black CI2 - White	
 7502 - 7500 Profile, white	 NO - No lens	 OX - Optiflex lens	 SWRD - Red loop SWPK - Pink loop SWCY - Cyan loop SWBK - Black loop SWBL - Blue loop SWWH - White loop SWGR - Green loop SWTR - Transparent loop SWOR - Orange loop	 Integrated driver & suspension kit See Appendix 2 on page 158 CIK0 - Alu CIK1 - Black CIK2 - White	
 750X - 7500 Profile, custom color IMPORTANT: Give RAL color No See Appendix 1 on page 158	 NO - No lens	 OP - Opal lens	 NO - No lens	 NO - No canopy	
RAL NUMBER					
PROFILE	LENS DOWN	LENS UP	MOUNTING HARDWARE	CANOPY	LENGTH

COLOR TEMPERATURE	LM PACKAGE DOWN/UP*	POWER CABLE FINISH	USAGE	POWERSUPPLY/CONTROL**	*NOTES	
 24 - 2400K  27 - 2700K  30 - 3000K  35 - 3500K  42 - 4200K  53 - 5300K (LHP only)  62 - 6200K (LP only)  WD1 - WarmDim 14W  WD2 - WarmDim 17W  TW1 - Tunable White 11W  TW2 - Tunable White 19W  RGB1 - RGB 14W  RGB2 - RGB 19W  RGBW1 - 3000K  RGBW2 - 3000K 4in1  NO - No up light (w/ opal lens)	LP0 - 128 LM / 1.5W FT / 90+CRI LP1 - 160 LM / 1.5W FT / 90+CRI LP2 - 255 LM / 3.0W FT / 90+CRI LP3 - 308 LM / 4.5W FT / 90+CRI LP4 - 400 LM / 5.8W FT / 90+CRI LHP - 700 LM / 7.0W FT / 95+CRI NO - No up light (w/ opal lens) Note: Not applicable for Warmdim Tunable White & RGB color temperatures	 BK - Black  WH - White  RD - Red  BC - Black/White Chevron	I - IP22 indoor dry location	A - Non-dimming B - ELV dimming 120V AC C - ELV dimming 120/277 VAC*** D - 0/10V dimming 120/277 VAC E - Non-dimming DC plug in F - DMX G - Lutron - HI-LUME PREMIER 0,1% Eco System 24V/96W I - Casambi CBU-A2D-0/10V-DALI-Bluetooth 100/277 VAC J - Casambi CBU-PWM4-4CH-Bluetooth 100/277 VAC K - Casambi CBU-TED-CV-Trail edge dim-Bluetooth 120 VAC NO - No driver	* The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and transluency conversion factors. ** By default both Up & Down LED engines are controlled from one source. For custom options, please contact your local representative. ***Only available in 96W - 24W Driver 	
CCT DOWN	CCT UP	LM DOWN	LM UP	POWER CABLE FINISH	USAGE	POWER SUPPLY/CONTROL

NOTES

