

6500 Profile


6500 (LM22800-01)



[AVAILABLE Q4 2016]

6000 Series

Dimensional drawing




Style and elegance in a compact format! The 6500 model is designed to accommodate a single lens in a very distinguished manner. It is designed to provide a thin tubular suspended lamp with a wide lighting angle.

Features

- Designed to give a uniform light without hot spots with an opal lens and a strip of 120 LEDs per meter or more.
- Compact aluminum profile of 20.5mm in diameter (with lens).
- Ideal for suspended lights.
- Custom length by sections of 2 to 240 inches (6m).
- Designed to meet North-American woodworking standards.
- Made of ALCOA 6063 T-5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED strip.
- Compatible with several installation accessories.

Options



LED strip compatibility

Compatible with LED strips up to **12mm** wide.























- B3528-xxV-60 - 8mm - 4.8W (95 lm/ft)
- B3528-xxV-120 - 8mm - 9.6W (220 lm/ft)
- B3528-xxV - 120H - 5mm - 9.6W (220 lm/ft)
- B3528-24V - 180H - 5mm - 14.4W (288 lm/ft)
- B5050-xxV-60 - 10mm - 14.4W (407 lm/ft)
- B5050-xxV-72 - 10mm - 17.8W (488 lm/ft)



6500 Profile

Components and accessories

6000 Series

PROFILE	LENSES	ENDCAPS	BRACKETS	ACCESSORIES	LENGTH
 <p>6500 Profile 6500 (LM22800-01)</p>	 <p>6500 Clear 6261 (LM22810-01)</p>	 <p>6500 endcap, Alu 6270 (LM22810-11 WITHOUT HOLE)</p>	 <p>Phantom 1290 (LM22310)</p>	 <p>Horz joiner straight 1325 (LM22335-01)</p>	<p>Custom length by sections of 2 to 240 inches (6m).</p>
 <p>6500 Profile Black 6501 (LM22800-02)</p>	 <p>6500 Optiflex 6262 (LM22810-03)</p>	 <p>6500 endcap, black 6271 (LM22810-15 WITHOUT HOLE)</p>	 <p>2 magnet kit 1316 (LM22330)</p>	 <p>Horz joiner 45° corner 1328 (LM22335-07)</p>	
	 <p>6500 Opal 6263 (LM22810-05)</p>		 <p>Susp. Kwik-Gripper 1/4"-20NC 1497 (LM22335-31)</p>	 <p>Horz joiner 90° corner 1326 (LM22335-03)</p>	
			 <p>Susp. Kwik-Gripper M10 X 1.0 1493 (LM22335-11)</p>	 <p>Vert joiner 90° corner 1327 (LM22335-05)</p>	
			 <p>Insert bracket M10 X 1.0 1494 (LM22335-15)</p>	 <p>Threaded tube M10 X 1.0 1511 (LM22335-40)</p>	
			 <p>Insert bracket 3/8"-16NC 1495 (LM22335-21)</p>	 <p>Threaded tube 3/8"-16NC 1512 (LM22335-41)</p>	
			 <p>Insert bracket 1/4"-20NC 1496 (LM22335-25)</p>	 <p>Threaded tube 1/4"-20NC 1513 (LM22335-42)</p>	
			 <p>Spring bracket 1570 (LM22336)</p>		

