

# How to order Mural 7420

## Wall Lighting

Client : \_\_\_\_\_ Project : \_\_\_\_\_

Order # : \_\_\_\_\_ Qty : \_\_\_\_\_ Date : \_\_\_\_\_

### HOW TO ORDER

Example of use MURAL7420 - 3 - UP/DOWN - 60 - 42K - OPTIFLEX - 12W - 120

MODEL	FINISH	ORIENTATION	LENGTH	CCT	LENS	POWER	VOLTAGE
MURAL7420	3 = ALU 0 = OTHER	UP/DOWN UP DOWN	19 = 19 INCH 39 = 39 INCH 60 = 60 INCH 72 = 72 INCH 96 = 96 INCH 0 = OTHER	30K = 3000K 35K = 3500K 42K = 4200K 0 = OTHER	SPREAD CLEAR OPTIFLEX OPAL	6W = 5.85W/FOOT 12W = 11.7W/FOOT 0 = OTHER	120 = 120VAC non-dimm. 120D = 120VAC dimm. 240 = 240VAC non-dimm. CV = Constant voltage, 12V or 24V

### Certifications



### Features

- Made in North America
- LED channel, finished in 6063 T-5 anodized aluminum, with endcap and installation on canopy. Other finishes available upon request.

### Lenses

