


9200 Profile (LUXSTRUT)

9200 (LM22950-10)



9000 Series

Cross-section dimensions:



The **9200** is our entry-level profile in the 9000 Series, designed for **surface mounted**, oversized linear lighting. It features a large surface area to install **multiple or oversized LED sources** for high output lighting, onto a heatsink inserted in one of several available slots, which in turn allows setting the needed beam angle. Its rugged construction makes the 9200 fit for **commercial and industrial applications**.

Features

- The ALCOA 6063-T5 aluminum alloy increases heat dissipation, for an extended lifetime of the LED source, and is suitable for outdoor installation.
- Custom length by sections of 2 to 240 inches (6m).
- 4 position slots for the LED heatsink insert for setting the needed beam angle.
- Accepts multiple or oversized LED sources on a 33mm (1.25in) wide area, for extra power. Has 3 application guides for 10mm (3/8-inch) wide LED strips.
- Designed to give a uniform light without hot spots when using an opal lens and a strip of 72 LEDs per meter or more.

Options



LED strip compatibility

Compatible with LED strips and PCBs up to **33mm** wide.

Linear weight














0.558 lbs/ft, 0.831 kg/m (without lens or insert)


















9200 Profile (LUXSTRUT)

Components and accessories

9000 Series

PROFILE	LENSES	ENDCAPS	BRACKETS	ACCESSORIES	LENGTH
 <p>9200 Profile 9200 (LM22950-10)</p>	 <p>9000 Clear 9547 (LM22960-7)</p>	 <p>9200-9400 endcap 9270 (LM22970-11) ALU 9272 (LM22970-15) BLACK 9274 (LM22970-20) WHITE</p>	 <p>9000 clip-in bracket 9571 (LM22980-1)</p>	 <p>Rail Insert 1.4 in. (37mm) 9000 (LM22954-99)</p>	<p>Custom length by sections of 6 to 240 inches (6m).</p>
 <p>9200 Profile Black 9512 (LM22950-2)</p>	 <p>9000 Optiflex 9541 (LM22960-1)</p>	 <p>9200 Susp. Kit with 15ft. aircraft cable 9289 (LM22320-89)</p>	 <p>1.5" stainless steel canopy kit for coax. wire (suspended) 4075 (LM22980-30)</p>		
 <p>9000 Opal 9543 (LM22960-3)</p>	 <p>5" canopy kit, fits standard 4" junction box 9484 (LM22980-21) ALU 9483 (LM22980-19) WHITE 9485 (LM22980-23) BLACK 9488 (LM22980-24) CHROME</p>				
 <p>9000 Focus 9545 (LM22960-5)</p>	 <p>7950 10" Canopy Kit 7950 (LM22840-50) ALU 7961 (LM22840-61) WHITE 7962 (LM22840-62) BLACK 7963 (LM22840-63) CHROME 7964 (LM22840-64) BRUSHED NICKEL</p>				
PROFILE	LENS	ENDCAPS	BRACKETS	ACCESSORIES	

Lumen package

LUMEN PACKAGE*	COLOR TEMPERATURE	LEAD LENGTH	USAGE	POWER SUPPLY TYPE	NOTES
 255 lm/ft, flex. 5/16" wide 12/24V Constant Voltage LP3528120	 Candle White 2400K	<p>Please specify the needed DC wire length (include units).</p>	 Indoor, dry (IP22) IP22	 Non-dimmable NO	<p>* The light output is provided in lumens per foot, for a CCT of 4200K and a clear lens. Please refer to the optics page for CCT and transluency conversion factors. ** Only available in CCTs of 3000K and 4200K, IP22, and lengths of 1/2/3/4/5/6/8 feet.</p>
 308 lm/ft, flex. 5/16" wide 24V Constant Voltage LP3528180	 Soft White 2700K		 Indoor, wet (IP68) IP68	 ELV dimming ELV	
 462 lm/ft, flex. 9/16" wide 24V Constant Voltage LP3528240	 Warm White 3000K		 Outdoor, weatherproof (IP68, NMWU, UV-resistant) IP68+	 0-10V dimming 0-10V	
 650 lm/ft, rigid 1/2" wide, 350/700mA Constant Current LP573052**	 Bright White 3500K				
	 Neutral White 4200K				
LUMEN PACKAGE	COLOR TEMPERATURE (CCT)	LEAD LENGTH	USAGE	POWER SUPPLY TYPE	

Notes

