

How to order 9400

Suspension & Wall-mounted Lighting

Client :

Project :

Order # :

Qty :

Date :

HOW TO ORDER

Example of use

MODEL	FINISH	LENGTH	CCT	LENS	MOUNT	USE	VOLTAGE
9400	3	36	30K	OPAL	SG18	OUT	120

MODEL	FINISH	LENGTH	CCT	LENS	MOUNT	USE	VOLTAGE
9400							
	3 = ALU 5 = BLACK 0 = OTHER	12 = 12 INCH (5W) 20 = 20 INCH (8W) 24 = 24 INCH (10W) 36 = 36 INCH (16W) 48 = 48 INCH (20W) 0 = OTHER	30K = 3000K 41K = 4100K	OPTIFLEX OPAL	SUSP/C = Susp. kit with canopy SUSP/S = Susp. kit without canopy WS=Wall support SW=Swivel wall support SG6=Sign 6 in. SG18=Sign 18 in.	IN=INDOOR OUT=OUTDOOR	120 = 120VAC non-dimm. 120D = 120VAC dimm. 240 = 240VAC non-dimm. CV = Constant voltage, 12V or 24V

Certifications



Finishes




Suspension



Features

- Made in North America
- ALCOA 6063T-5 Aluminum
- Guideline for easy installation
- Dimmable (use Lutron CTCL-153P-Skylark or Diva)



Lenses

