


# BLAZE

Recessed swivel spotlight bar



## Luminaires

Cross-section dimensions:



The **BLAZE** is a modular recessed lighting system composed of **multiple swiveling spotlights**. Each spotlight can swivel up to 30 degrees and rotate 360 degrees, allowing for a **precise lighting control**. The recessed enclosure, with a rugged build in anodized aluminum and 12-gauge steel, also houses the power supplies. Spring brackets make installation a breeze. An excellent solution for retail spaces, showrooms, galleries, due to its small footprint, modern design, and sensible finishing.

### Options



### LED strip compatibility


The BLAZE system uses proprietary LED light sources and is incompatible with LED strips.

### Features



- Recessed luminaire comprised of 5 or 10 individually swiveling LED lights, each with 30° beam, 2W power, 160 lumen output, and CRI>80.
- 3/4-inch flanges provide generous clearance for a perfectly aligned, easy and secure installation in suspended/plasterboard ceilings and walls via spring brackets.
- Rugged build in 6063-T5 aluminum and 12-gauge steel with a low (1/4-inch) surface offset.
- Includes seismic safety braided metal cable with loop, and power supply in junction box.
- Can be installed in direct contact with insulation.
- Available in white trim and and black interior finish, 120VAC input, dimming.



**BLAZE 10:** 27.5 x 4.1 in (698 x 105 mm)  
Hole: 26.5 x 3.1 in



**BLAZE 5:** 14.5 x 4.1 in (368 x 105 mm)  
Hole: 13.5 x 3.1 in



Swivel spotlight unit

# BLAZE



Components and accessories

# Luminaires



## LUMINAIRE

## NOTES



-  BLAZE 5, 120VAC Input, ELV Dimming 3000K (Warm White), 10W / 800 LM **5221** (LM65222-05)
-  BLAZE 5, 120VAC Input, ELV Dimming 4200K (Neutral White) 10W / 800 LM **5223** (LM65222-25)



-  BLAZE 10, 120VAC Input, ELV Dimming 3000K (Warm White), 20W / 1600 LM **5222** (LM65222-10)
-  BLAZE 10, 120VAC Input, ELV Dimming 4200K (Neutral White), 20W / 1600 LM **5224** (LM65222-20)

Also available in non-dimming 277VAC or 347VAC input variants, details upon inquiry. Minimum order quantities apply.

## LUMINAIRE

# Notes

