


1550 Profile

1550 (LM22235-01)



1000 Series

Dimensional drawing



Here is a solution for the **easiest bidirectional light washing** ever. Whether illuminating art from behind the frame, adding a halo around a panel, lighting a cove or a vanity mirror from the perimeter, the 1550 profile will do a rock-solid job, fine-tuned to your liking, while staying, well, “behind the curtain.”

Features

- An axially-symmetrical double profile accepting 2 light sources, projecting the light laterally in both directions.
- Developed for a concealed installation between two parallel surfaces.
- Will provide a uniform light without hot spots with an opal lens and a strip of 120 LEDs per meter or more.
- The protruding edges allow for a solid attachment to most surfaces and/or panels, permanently via your choice of standard hardware, or easily removable when using our standard 1000-Series surface mounting brackets.
- Custom length by sections of 2 to 240 inches (6m).
- Application guide for 10mm (3/8-inch) LED strip or less.
- Designed to meet North American woodworking standards.
- Made of ALCOA 6063 T-5 aluminum alloy for improved heat dissipation and increased LED strip lifetime.

Options



LED strip compatibility

Compatible with LED strips up to **14mm** wide.














- B3528-xxV-60 - 8mm - 4.8W (95 lm/ft)
- B3528-xxV-120 - 8mm - 9.6W (220 lm/ft)
- B3528-xxV - 120H - 5mm - 9.6W (220 lm/ft)
- B3528-24V - 180H - 5mm - 14.4W (288 lm/ft)
- B3528-xxV-240 - 14mm - 19.5W (410 lm/ft)
- B5050-xxV-60 - 10mm - 14.4W (407 lm/ft)
- B5050-xxV-72 - 10mm - 17.8W (488 lm/ft)



1550 Profile

Components and accessories

1000 Series

PROFILE	LENSES	BRACKETS	ACCESSORIES	LENGTH
 <p>1550 Profile 1550 (LM22235-01)</p>	 <p>Standard, Clear 1269 (LM22298)</p>  <p>Standard, Spread 1265 (LM22294)</p>  <p>Standard, Optiflex 1261 (LM22290)</p>  <p>Standard, Opal 1263 (LM22292)</p>  <p>Standard, Focus 1267 (LM22296)</p>	 <p>Flat bracket 1280 (LM22306)</p>  <p>Phantom 1290 (LM22310)</p>	 <p>Horz joiner straight 1325 (LM22335-01)</p>  <p>Horz joiner 45° corner 1328 (LM22335-07)</p>  <p>Horz joiner 90° corner 1326 (LM22335-03)</p>  <p>Vert joiner 90° corner 1327 (LM22335-05)</p>  <p>Surface mounting profile 1556 (LM22235-10)</p>	<p>Custom length by sections of 2 to 240 inches (6m).</p>
<p>1550</p> <p>PROFILE</p>	<p>LENS</p>	<p>BRACKETS</p>	<p>ACCESSORIES</p>	<p>LENGTH</p>