


1000 Series

Dimensional drawing

















A sleek rounded profile especially **designed to conceal brackets and wires**. The 1690 is mostly used under cabinets. It can also serve many other purposes, such as mural fixtures.

Features

- Designed to give a uniform light without hot spots* with an opal lens and a strip of 120 LEDs per meter or more.
- Custom length by sections of 2 to 240 inches (6m).
- Application guide for 10mm (3/8-inch) LED strip or less.
- Designed to meet North-American woodworking standards.
- Made of ALCOA 6063 T-5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED strip.
- Compatible with several installation accessories.

Options











LED strip compatibility

Compatible with LED strips up to 14mm wide.

- B3528-xxV-60 8mm 4.8W (95 lm/ft)
- B3528-xxV-120 8mm 9.6W (220 lm/ft)
- B3528-xxV 120H 5mm 9.6W (220 lm/ft)
- B3528-24V 180H 5mm 14.4W (288 lm/ft)
- B3528-xxV-240 14mm 19.5W (410 lm/ft)
- B5050-xxV-60 10mm 14.4W (407 lm/ft)
- B5050-xxV-72 10mm 17.8W (488 lm/ft)



1000 Series

1690 Profile

Components and accessories

PROFILE	LENSES	ENDCAPS	BRACKETS	LENGTH	
				Custom length by sections of 2 to 240 inches (6m).	
1690 Profile 1690 (LM22250)	Standard, Clear 1269 (LM22298)	1690 endcap, Alu 1695 (LM22250-05 WITHOUT HOLE) 1691 (LM22250-01 HOLE)	Flat bracket 1280 (LM22306)		
1690 Profile, black 1691 (LM22250-01)	Standard, Spread 1265 (LM22294)	1690 endcap, black 1696 (LM22250-06 WITHOUT HOLE) 1698 (LM22250-08)			
	Standard, Optiflex 1261 (LM22290)				
	Standard, Opal 1263 (LM22292)				
1690	-	-		_	-
PROFILE	LENS	ENDCAPS	BRACKETS	ACCESSORIES	LENGTH