

How to order Sign 7450

Wall Lighting & Signage

Client :	Project :	
Order # :	Qty :	Date :

HOW TO ORDER

Example of use

MODEL	FINISH	ORIENTATION	LENGTH	CCT	LENS	POWER	CUSTOM SIGNAGE	VOLTAGE
SIGN7450	3	UP/DOWN	60	42K	OPTIFLEX	12W	CD	120

MODEL	FINISH	ORIENTATION	LENGTH	CCT	LENS	POWER	CUSTOM SIGNAGE	VOLTAGE
SIGN7450								
	3 = ALU 0 = OTHER	UP/DOWN UP DOWN	19 = 19 INCH 39 = 39 INCH 60 = 60 INCH 72 = 72 INCH 96 = 96 INCH 0 = OTHER	30K = 3000K 35K = 3500K 42K = 4200K 0 = OTHER	SPREAD CLEAR OPTIFLEX OPAL	6W = 5.85W/FOOT 12W = 11.7W/FOOT 0 = OTHER	ND = NO SIGNAGE CD = CUSTOM SIGNAGE DESIGN* *Ask your sales rep.	120 = 120VAC non-dimm. 120D = 120VAC dimm. 240 = 240VAC non-dimm. CV = Constant voltage, 12V or 24V

Certifications



Features

- Made in North America
- Two LED channels
- Finished in 6063 T-5 anodized aluminum, with endcap and installation on canopy. Other finishes available upon request.
- Possibility of CNC machining of front plate, engraving or printing, and backlighting through acrylic panel for custom signage.

Lenses

