## **How to order TruZZ**

Suspension Lighting

Client :			Project :			
Order # :		Qty:			Date :	
HOW TO ORDER		Example of use	MODEL FINISH TRUZZ - 3 -	CCT LENS 30K - OPAL -	SUSP/C - 120	- C
MODEL FINISH  TRUZZ - 3 = ALU 5 = BLACK  O = OTHER	CCT  - 30K = 3000K 41K = 4100K	OPTIFLEX OPAL	SUSP/C = Susp. kit with canopy SUSP/S = Susp. kit without canopy	VOLTAGE  120 = 120VAC non-dimm. 120D = 120VAC dimm. 240 = 240VAC non-dimm.  CV = Constant voltage, 12V or 24V	BW = BLACK & WHI R = BRAIDED RED W = WHITE C = CLEAR	
Certifications	Finishes		Suspension		Electrical Wire	
MADE IN COLORA CONTROL					Black & White	(33333333333333
Features  Made in North America	Black	Aluminum	Canopy rect. 14 in	able driver	Braided Red	
Anodized ALCOA 6063T-5 Alumin Guideline for easy installation View angle 90° Dimmable (with remote driver on	i–	1,625 in. 41,28 mm	Remote driver		Black	_
use Lutron CTCL-153P-Skylark or Suspension wire up to: 15' / 4.5 r	Diva) n	1,625 in. 11,28 mm	With dimmable remote drive	12"	White	
Lenses			24* 24*	12"   48"	Clear	
9000 Optiflex 9541 (LM22960-1) 9543 (LM22960-3)			12" 72" 72"	<b>→</b>		
			Z			
+						