

### 1000 Series

Dimensional drawing















Here is a **compact and recessed** profile allowing you to make the light source and the LED invisible\*. The edges on each side of this extrusion allow recessed installation giving it style with a discreet and neat appearance.

#### **Options**









#### **Features**


- Designed to give a uniform light without hot spots\* with an opal lens and a strip of 120 LEDs per meter or more.
- The edge allows recessed installation. To be installed in a 19mm (3/4-inch) groove.
- Custom length by sections of 2 to 240 inches (6m).
- · Application guide for 10mm (3/8-inch) LED strip or less.
- Designed to meet North-American woodworking standards.
- Made of ALCOA 6063 T-5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED strip.
- · Compatible with several installation accessories.

### LED strip compatibility

Compatible with LED strips up to 14mm wide.

- B3528-xxV-60 8mm 4.8W (95 lm/ft)
- B3528-xxV-120 8mm 9.6W (220 lm/ft)
- B3528-xxV 120H 5mm 9.6W (220 lm/ft)
- B3528-24V 180H 5mm 14.4W (288 lm/ft)
- B3528-xxV-240 14mm 19.5W (410 lm/ft)
  B5050-xxV-60 10mm 14.4W (407 lm/ft)
- B5050-xxV-72 10mm 17.8W (488 lm/ft)





# 1000 Series

## 1300 Profile

Components and accessories

PROFILE	LENSES	ENDCAPS	BRACKETS	LENGTH
			20	Custom length by sections of 2 to 240 inches (6m).
1300 Profile 1220 (LM22210)	Standard, Clear <b>1269</b> (LM22298)	Standard 1300 1274 (LM22301-05 WITHOUT HOLE	Flat bracket <b>1280</b> (LM22306)	
		1277 (LM22301-01 HOLE)		
	Standard, Spread <b>1265</b> (LM22294)		45° bracket 1283 (LM22307)	
	Standard, Optiflex			
	<b>1261</b> (LM22290)		Swivel Bracket 180° <b>1286</b> (LM22308)	
	Standard, Opal <b>1263</b> (LM22292)			
1220	-	-	-	_
PROFILE	LENS	ENDCAPS	BRACKETS	LENGTH