


5350 Profile

5350 (LM22520)



5000 Series

Dimensional drawing



Here is a **compact and recessed** profile allowing you to make the light source and the LED invisible*. The edges on each side of this extrusion allow recessed installation giving it style with a discreet and neat appearance.

Features

- Designed to give a uniform light without hot spots* with an opal lens and a strip of 120 LEDs per meter or more.
- The edge allows recessed installation. To be installed in a 19mm (3/4-inch) groove.
- Custom length by sections of 96 inches (2.44m).
- Application guide for 10mm (3/8-inch) LED strip or less.
- Designed to meet North-American woodworking standards.
- Made of ALCOA aluminum alloy 6063 T-5 increasing heat dissipation.
- Its use increases the lifetime of your LED strip.
- Compatible with several installation accessories.

Options



LED strip compatibility

Compatible with LED strips up to **10mm** wide.




- B3528-xxV-60 - 8mm - 4.8W (95 lm/ft)
- B3528-xxV-120 - 8mm - 9.6W (220 lm/ft)
- B3528-xxV - 120H - 5mm - 9.6W (220 lm/ft)
- B3528-24V - 180H - 5mm - 14.4W (288 lm/ft)
- B5050-xxV-60 - 10mm - 14.4W (407 lm/ft)
- B5050-xxV-72 - 10mm - 17.8W (488 lm/ft)



5350 Profile

Components and accessories

5000 Series

PROFILE	LENSES	ENDCAPS	LENGTH
 5350 Profile 5350 (LM22520)	 5350 Opal 5040 (LM22520-40)	 Standard 5350 Alu 5005 (LM22520-05 WITHOUT HOLE) 5001 (LM22520-01 HOLE)	Custom length by sections of 2 to 96 inches (2.44m).

