

# How to order SERZO

## Suspension Lighting

Client :

Project :

Order # :

Qty :

Date :

### HOW TO ORDER

Example of use  -  -  -  -  -  -  -

MODEL	DIAMETER	DIFFUSER	CCT	FINISH	POWER	VOLTAGE	ELECTRICAL WIRE
SERZO	36 = 36 INCH 54 = 54 INCH 72 = 72 INCH	OPAL	30K = 3000K 41K = 4100K	ALU = Aluminum WH = White CH = Charcoal	19.5 = 19.5W/m 39 = 39W/m (double row)	120 = 120VAC non-dimm. 120D = 120VAC dimm. 240 = 240VAC non-dimm. CV = Constant voltage, 12V or 24V	BW = BLACK & WHITE R = BRAIDED RED W = WHITE C = CLEAR


### Certifications



### Finishes




### Central Canopy



12 in. rect. canopy

Includes internal non-dimmable driver



External remote driver

With dimmable remote driver only

### Electrical Wire

Black & White

Braided Red

Black

White

Clear

### Features

- Made in North America
- ALCOA 6063T-5 aluminium, stainless steel, opal acrylic diffuser-reflector
- Guideline for easy installation
- 360° lighting
- Includes canopy and 3x15 ft (4,5m) of braided stainless steel suspension cable
- Dimmable (with remote driver only - use Lutron CTCL-153P-Skylark or Diva)

