

This LED profile is easy to install and ideal for **residential**, **commercial and industrial projects**. Built in 6063 T-5 aluminum, our DEL extrusion can be installed in **dry or humid locations**. It can also be painted to match your decor. Available in lengths of 20 feet, you can create the desired effect, even in larger spaces and heights. **This profile can be surface mounted**.

## Options



## LED strip compatibility

Compatible with LED strips up to **33mm** wide.

- B3528-xxV-60 8mm 4.8W (95 lm/ft) 1-3 strips
- B3528-xxV-120 8mm 9.6W (220 lm/ft) 1-3 strips
- B3528-xxV 120H 5mm 9.6W (220 lm/ft) 1-3 strips
  B3528-24V 180H 5mm 14.4W (288 lm/ft) 1-3 strips
- B3528-xxV-240 14mm 19.5W (410 lm/ft) 1-2 strips
- B5050-xxV-60 10mm 14.4W (407 lm/ft) 1-3 strips
- B5050-xxV-72 10mm 17.8W (488 lm/ft) 1-3 strips
- Designed to give a uniform light without hot spots with an opal lens and a strip of 72 LEDs per meter or more.
- Custom length by sections of 2 to 240 inches (6m).
- 3 application guides for 10mm (3/8-inch) or narrower LED strips.
- Possibility to install 2 strips of 14mm for even more power.
- Made of ALCOA 6063 T-5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED strip.
- Compatible with several installation accessories.
- Suitable for outdoor installation.

**Features** 

• Has 3 position slots for the LED strip tray insert (the closer the strip is to the lens, the higher the chances of seeing the bright spots).









48

## 9200 Profile (LUXSTRUT)

Components and accessories

## 9000 Series



