How to order TruZZ

Suspension Lighting

client :			Project :			
Order # :		Qty:			Date :	
OW TO ORDER		Example of use	MODEL FINISH CCT TRUZZ - 3 - 30K	- OPAL -	MOUNT VOLTAGE SUSP/C - 120	electrical wire
### TRUZZ -	30K = 3000K 41K = 4100K	OPTIFLEX OPAL	canopy 120 SUSP/S = Susp. kit without 240 canopy	VOLTAGE = 120VAC non-dimm. D = 120VAC dimm. = 240VAC non-dimm. = Constant voltage, 12V or 24V	BW = BLACK & WHI R = BRAIDED RED W = WHITE C = CLEAR	
ertifications <u>Finishes</u>		Suspension		1	Electrical Wire	
6063-T5 CNUS RELEGION COMPANY	Black	Aluminum			Black & White	(((((((((((((((((((((((((((((((((((((((
Made in North America Anodized ALCOA 6063T-5 Aluminum Guideline for easy installation View angle 90° Dimmable (with remote driver only - use Lutron CTCL-153P-Skylark or Diva) Suspension wire up to: 15' / 4.5 m Lenses		Aldillildill	Canopy rect. 14 in Includes internal non-dimmable d	iriver	Braided Red	
		1,625 in. 41,28 mm	Remote driver		Black	
		1,625 in. 41,28 mm	With dimmable remote driver only	/ 12" 2"	White	
			24"	48"	Clear	
9000 Optiflex 9541 (LM22960-1) 9000 Opal 9543 (LM22960-3)			12" 72"	→		
			Z			