

B5050-24V-72-10mm-17.8W-3500K-IP22

Specification Sheet



PHYSICAL

Product Type	Flexible LED Strip		
SMD Type	5050		
Strip Width	2/5 in	10 mm	
Strip Total Length (Roll)	16.4 ft	5 m	
LED Linear Density	21.9 LED/ft	72 LED/m	360 LED/roll total
Can be cut at every	1.09 in	27.8 mm	2 LED
Lifespan	50 000 Hrs		
IP Code (IEC standard 60529)	IP22		

ELECTRICAL

Input Type	DC, Constant Voltage		
Input Voltage	24V DC		
Rated Power (Max.)	5.4 W/ft	17.8 W/m	89 W/roll total

LIGHTING

Luminous Flux	372.9 lm/ft	1223.6 lm/m	6118 lm/roll total
Luminous Efficacy	80.5 lm/W		
Correlated Color Temperature	3500K (Bright White)		
Colour Rendering Index	93.2		
R9	87		
duv (black-body curve deviation)	0.0010		




Electrical Input

Rated Power (Max.)


CONSTANT VOLTAGE	24V DC	89 W/roll
------------------	---------------	------------------

Correlated Color Temperature (CCT)

3500K



DIMENSIONS



B5050-24V-72-10mm-17.8W-3500K-IP22

Test Data for 1 Meter LED Strip Length



Chroma Parameters

Chromaticity Coordinates: $x=0.3981, y=0.3893, u=0.2316, v=0.3397, duv=0.0010$
 Correlated Color Temperature: 3624K
 Dominant Wave.: 579.9nm
 Purity: 36.3%
 Flux RGB Ratio: R=19.7%, G=78.0%, B=2.3%
 Peak Wave: 595.6nm
 Half Width: 147.4nm

Rendering Index: Ra=93.2

R1=95 R2=92 R3=93 R4=94 R5=94 R6=91 R7=96 R8=97
 R9=87 R10=81 R11=95 R12=74 R13=96 R14=95 R15=98


Photo Parameters

Luminous Flux: 1223.6 lm
 Luminous Efficacy: 80.5 lm/W
 Radiant Flux: 3651.7 mW
 Iv: 0.0 mcd


Electrical Parameters

Voltage: U=24.000V
 Current: I=0.63A
 Power: P=15.20W
 Power Factor: PF=1.000

C.I.E. 1931 Chromaticity Diagram



Binning: G135-36 (3550-3650K)



Spectral Ratio: R=36.2%, G=47.4%, B=16.5%

