


B5050-24V-60-10mm-14.4W-RGB-IP22/IP68

Specification Sheet



PHYSICAL

Product Type	Flexible LED Strip		
SMD Type	5050		
Strip Width	2/5 in	10 mm (IP22)	12 mm (IP68)
Strip Total Length (Roll)	16.4 ft	5 m	
LED Linear Density	18.3 LED/ft	60 LED/m	300 LED/roll total
Can be cut at every	3.94 in	100 mm	6 LED
Storage / Operating Temp.	-40°C to +80°C	-25°C to +40°C	
Lifespan	50 000 Hrs		



Electrical Input

Rated Power (Max.)

CONSTANT
VOLTAGE**24V DC****72 W/roll**

ELECTRICAL

Input Type	DC, Constant Voltage		
Input Voltage	24V DC		
Rated Power (Max.)	4.4 W/ft	14.4 W/m	72 W/roll total

PRODUCT RANGE

Part Number	Code	IP	CCT*	Flux RGB Ratio	Luminous Flux	Luminous Efficacy	CRI**	duv***
B5050-24V-60-10mm-14.4W-RGB-IP22	LM28336	IP22	RGB	R=27.1% G=64.3% B=8.6%	1154.7 lm	18.17 lm/W	20.3	-0.0018
B5050-24V-60-10mm-14.4W-RGB-IP68	LM28338	IP68						

CCT* - Correlated Color Temperature
 CRI** - Colour Rendering Index
 duv*** - Black-body Curve Deviation

Office & Showroom:
 6068 Metropolitain East, Montreal, Quebec, H1S 1A9, Canada

Toll Free: 1-855-384-3384
 E-mail: info@lumentruss.com
 www.lumentruss.com

Copyright Lumentruss, All Rights Reserved
 Lumentruss reserves the right to make changes to this product
 without advance notice, and any such change shall be effective immediately

B5050-24V-60-10mm-14.4W-RGB-IP22/IP68

Test Data for 1 Meter LED Strip Length



Chroma Parameters

Chromaticity Coordinates: $x=0.2587, y=0.2275, u=0.1985, v=0.2619, duv=-0.018$
 Correlated Color Temperature: 50000K
 Dominant Wave.: 468.3nm
 Purity: 36.9%
 Flux RGB Ratio: R=27.1%, G=64.3%, B=8.6%
 Peak Wave: 633nm
 Half Width: 18.4nm

Rendering Index: Ra=20.3

R1=-6 R2=40 R3=65 R4=5 R5=17 R6=38 R7=50
 R8=-43 R9=-338 R10=-47 R11=-22 R12=45 R13=0 R14=73

Photo Parameters

Luminous Flux: 1154.7 lm
 Luminous Efficacy: 18.17 lm/W

Electrical Parameters

Voltage: U=24.000V
 Current: I=0.560A
 Power: P=13.44W
 Power Factor: PF=1.000

C.I.E. 1931 Chromaticity Diagram

